Comparison Testers

Hydraulic

GCL / GCH Series

Portable / Bench-top Models

Screw Pumps

Useful for checking Pressure Measuring Devices / Master Devices / Test Gauges

SALIENT FEATURES

Bud		

Very Low Maintenance Cost

Compact & Easy to carry for Lab & Field use

Priming Pump with Fine Adjustment Vernier for Incremental Pressure generation

Adjustable Foot

SPECIFICATIONS


Ranges	0 to 250 / 350 (GCL-SP Series). 0 to 700 / 1000 bar (GCH-SP Series)		
Туре	Screw Pump		
Pressure generation	Priming Pump for initial pressures & Screw RAM Pump for high pressures		
Test Port Connection	1/2" BSP (F) Swivel		
Medium	Oil (Optional : Water) #		
Dimensions	370 x 410 x 230 mm (L x D x H)		
Weight	14 Kg.		

STANDARD INCLUSIONS

- Basic Instrument
- Hydraulic Fluid (500 ml)
- Set of Seals
- Conformance Certificate
- Instruction Manual

OPTIONAL (ADD-ON) ITEMS

- Analog or Digital Master Gauges
- Distilled Water #



Right Angled & Two Gauge Adaptors



Typical Photo; Final product look may vary

Manufactured by

NAGMAN INSTRUMENTS & ELECTRONICS (P) LTD.

Chei
Chei
Dom

Chennai-Bangalore National Highway, Nazarathpet P.O., Chembarambakkam, Chennai – 600 123. INDIA.

AN ISO 9001:2015 CERTIFIED COMPANY

E-Mail: mktgchennai@nagman.com

 Domestic Sales
 Phone: 044 – 66777020, 005, 021, 024.
 Fax: 044 – 66777050.

 Export Sales
 Phone: +91-44-66777006, 008.
 Fax: +91-44-66777050.

Fax: +91-44-66777050. E-Mail: exports@nagman.com www.nagman.com

NIE/TDS/GCL/GCH/01/00

Specifications subject to change owing to continuous development. Contact us for latest Datasheet.