

Dead Weight Testers

Hydraulic

H6000

Bench-top / Table-top Model

Ideal for Fine Increments & for Medium Volume Calibration. Ensures – Easy & Controllable Pressure generation for Calibrating Pressure Gauges / Transducers / Transmitters, Transfer Standards, Recorders, Digital Calibrators etc.

Screw Pump with built-in Priming Pump

SALIENT FEATURES

Engineering Units : bar or Kg/Cm² or psi (Kpa & Mpa also available)
Adjustable Foot & Spirit Level
Piston Calibrated thro' "Cross Floating Techniques"
Calibrated to Standard Gravity
(Optional : Calibration to Local Gravity as per Customer's requirement)
Accuracies Traceable to International Standards
Non-Magnetic Stainless Steel Weight Sets
Motorized Model – Optional



* Accessories shown above are not part of standard equipment

SPECIFICATIONS

Ranges	35 / 70 / 100 / 160 / 350 / 600 / 700 bar	
Piston	Single / Dual	} Refer Table 2
Standard Accuracy	±0.05% of Reading	
Traceability	International Standards	} Refer Table 1
Weights	Non-Magnetic Stainless Steel	
Pressure generation	Thro' Priming Pump & Screw Ram	
Standard Corrections	Gravity : 9.80665 m/s ² * / Temperature : 23°C / Air Density : 1.2 Kg/Cm ²	
Weight (approx.)	Instrument : 19 Kg. ; Weight Sets : 8 to 33 Kg.	Refer Table 2
No. of Weights	12 to 15	
Instrument Dimensions	530 x 390 x 230 mm (L x W x H)	
Operating Fluid	Oil	
DWTCal Software	Optional	

Table 1

Model	Accuracy	PCU	Weight Set	Certification	Remarks
H6000	±0.05% of Reading	Tungsten Carbide Piston & Matching Cylinder	Non-Magnetic Stainless Steel	Overall Accuracy	Traceable to ISO/IEC 17025:2017 Accredited Calibration Lab

Table 2

Piston Type	Piston Model	Pressure Ranges		
		1 / Bar	2 / Kg/Cm ²	3 / PSI
Single	SP-35	0.5 to 35	0.5 to 35	10 to 500
Single	SP-70	0.5 to 70	0.5 to 70	10 to 1000
Single	SP-100	5 to 100	5 to 100	75 to 1500
Single	SP-160	5 to 160	5 to 160	75 to 2500
Single	SP-350	5 to 350	5 to 350	75 to 5000
Single	SP-600	10 to 600	10 to 600	150 to 9000
Single	SP-700	10 to 700	10 to 700	150 to 10000
Dual	DP-160	1 to 160	1 to 160	15 to 2500
Dual	DP-350	1 to 350	1 to 350	15 to 5000
Dual	DP-600	1 to 600	1 to 600	15 to 9000
Dual	DP-700	1 to 700	1 to 700	15 to 10000

STANDARD INCLUSIONS

- Basic Instrument
- Calibrated S.S Weight Sets - Refer Table 1 & 2
- Full set of Adaptors consisting of 1/8", 1/4", 3/8", 1/2" BSP (Set of NPT Adaptors available on request)
- Operating Fluid (500 ml)
- Spirit Level, Pointer Puller / Punch
- Set of Spanners & Screw Driver
- 'O' Ring & Seals
- Dust Cover, Wooden Carrying Case (for Weight Sets)
- Traceable Calibration Certificate
- Instruction Manual

OPTIONAL (ADD-ON) ITEMS

- Right angled Adaptor
- Two Gauge Adaptor
- Conversion Weight Sets to convert from one unit of Pressure to another
- Incremental Weight Sets for smaller increments of Pressure
- DWTCal Calibration Software
- Motorized Version
- Calibration Certificates are issued in Accordance with our Scope as granted by NABL per ISO/IEC 17025:2017 Standards - Refer Table 1



Manufactured by

NAGMAN INSTRUMENTS & ELECTRONICS (P) LTD.

*Chennai-Bangalore National Highway, Nazarethpet P.O., Chembarambakkam,
Chennai – 600 123. INDIA.*

**AN ISO 9001:2015
CERTIFIED COMPANY**

Domestic Sales Phone : 044 – 66777020, 005, 021, 024. Fax : 044 – 66777050. E-Mail : mktgchennai@nagman.com
Export Sales Phone : +91-44-66777006, 008. Fax : +91-44-66777050. E-Mail : exports@nagman.com

www.nagman.com

Specifications subject to change owing to continuous development. Contact us for latest Datasheet.

NIE/TDS/H6000/01/00

Feb. 2021