Technical Datasheet Portable Dual Pressure Calibrator PPC-D Heavy Duty - Dual - Pneumatic & Hydraulic Table-top / Bench-top Ideal Lab / Site Tool for checking & Calibration of Pressure / Differential Pressure Gauges / Transmitters / Indicators / Loops, Pneumatic Receiver Gauges, Control Valves, Pressure / Transducers etc.- in Industrial & Marine Applications SALIENT FEATURES DNV.GI Light Weight & Compact Unique Combo 2-in-1 Space Saver Housed in Rugged Carry Case Automatic Temperature Compensation (0 to 50°C) Large Graphic Display Touch Membrane Keypad Selectable Engineering Pressure Units DC Current & Voltage Measurement Switch Test capability & Zero Offset facility Audio & Visual Alarms for Over Pressure Pressure Transducer – all Media compatible with SS316 Rechargeable Battery with 'Low Battery' indication

Digital Pressure Indicator with 2 integral / built-in Pumps & Fine Adjustment Vernier



SPECIFICATIONS

| Ranges | -0.85 bar Vacuum to 20 bar (Pneumatic) & 0 to 400 bar (Hydraulic) (Oil) | |
|----------------------------|---|--|
| Accuracy | ±0.05% F.S. | |
| Temperature Compensation | 0 to 50°C (Automatic) | |
| Display Resolution | Minimum 5 digits | |
| Display | Large Graphic Display | |
| Engineering Units | Kg/cm2, bar, mbar, PSI, mH2O, mmH2O, cmH2O, inH2O, ftH2O, mmHg, inHg, Atm, Mpa, Kpa, Pa | |
| mA Input | 50 mA (Active Loop) & 25 mA (Passive Loop) | |
| Volt Input | 0 to 30V DC | |
| Resolution (mA / V) | 0.001 | |
| Pressure Switch Test | Maximum 5V DC (approx.) | |
| Medium | Air & Oil (Water : optional) # | |
| Over Pressure Alarm | 120% FS (Audio / Visual) | |
| Instrument Dimension | 425 x 335 x 200 mm (L x B x H) | |
| Instrument Weight (approx) | 10 Kg. | |

| STANDARD INCLUSIONS | | | |
|-----------------------------|-----------------------------------|--------------------|--|
| Digital Pressure Calibrator | Hose with End Fitting (Pneun | natic & Hydraulic) | |
| Test Leads & Seals Kit | External Charger | | |
| Oil : 250 ml | Traceable Calibration Certificate | | |
| Instruction Manual | Computer Interface | | |
| Set of Adaptors | BSP | <u>NPT</u> | |

1/8" BSP(F) X 1/4" BSP (M)

1/2" BSP(F) X 1/4" BSP (M)

3%" BSP(F) X ¼" BSP (M)

OPTIONAL (ADD-ON) ITEMS

"Calpress" Calibration Software with Cable

Calibration Certificates are issued in Accordance with our Scope as granted by NABL per ISO/IEC 17025:2017 Standards

Water Operated #

Manufactured by



Chennai-Bangalore National Highway, Nazarathpet P.O., Chembarambakkam, Chennai - 600 123. INDIA.

NAGMAN INSTRUMENTS & ELECTRONICS (P) LTD.

1∕₃" NPT(F) X 1⁄₄" BSP (M)

¼" NPT(F) X ¼" BSP (M)

1/2" NPT(F) X 1/4" BSP (M) ¾" NPT(F) X ¼" BSP (M)

Domestic Sales Phone : 044 – 66777020, 005, 021, 024. **Fax** : 044 – 66777050. **Phone** : +91-44-66777006, 008. Export Sales

Fax : +91-44-66777050. www.nagman.com

AN ISO 9001:2015 **CERTIFIED COMPANY**

E-Mail : mktgchennai@nagman.com E-Mail: exports@nagman.com

Specifications subject to change owing to continuous development. Contact us for latest Datasheet.

NIE/TDS/PPC-D/01/00

Feb. 2021