Portable Dual Pressure Calibrator

Heavy Duty - Dual - Pneumatic & Hydraulic

PPC-D+ Table-top / Bench-top

Ideal Lab / Site Tool for checking & Calibration of Pressure / Differential Pressure Gauges / Transmitters / Indicators / Loops, Pneumatic Receiver Gauges, Control Valves, Pressure / Transducers etc.- in Industrial & Marine Applications

SALIENT FEATURES

Light Weight & Compact
Unique Combo 2-in-1 Space Saver
Housed in Rugged Carry Case
Automatic Temperature Compensation (0 to 50°C)
Large Graphic Display
Touch Membrane Keypad
Selectable Engineering Pressure Units
DC Current & Voltage Measurement
Switch Test capability & Zero Offset facility
Audio & Visual Alarms for Over Pressure
Pressure Transducer – all Media compatible with SS316
Rechargeable Battery with 'Low Battery' indication
Digital Pressure Indicator with 2 integral / built-in Pumps & Fine Adjustment Vernier



SPECIFICATIONS

Ranges	-0.85 bar Vacuum to 20 bar (Pneumatic) & 0 to 400 bar (Hydraulic) (Oil)		
Accuracy	±0.025% F.S.		
Temperature Compensation	0 to 50°C (Automatic)		
Display Resolution	Minimum 5 digits		
Display	Large Graphic Display		
Engineering Units	Kg/cm2, bar, mbar, PSI, mH2O, mmH2O, cmH2O, inH2O, ftH2O, mmHg, inHg, Atm, Mpa, Kpa, Pa		
mA Input	50 mA (Active Loop) & 25 mA (Passive Loop)		
Volt Input	0 to 30V DC		
Resolution (mA / V)	0.001		
Pressure Switch Test	Maximum 5V DC (approx.)		
Medium	Air & Oil (Water : optional) #		
Over Pressure Alarm	120% FS (Audio / Visual)		
Instrument Dimension	425 x 335 x 200 mm (L x B x H)		
Instrument Weight (approx.)	10 Kg.		

	STANDARD INCL	USIONS	OPTIONAL (ADD-ON) ITEMS
Digital Pressure Calibrator	or Hoses with End Fitting (Pneumatic & Hydraulic)		"Calpress" Calibration Software with Cable
Test Leads & Seals Kit	Oil: 250 ml		
External Charger	Computer Inter	face	Water Operated #
Instruction Manual	Calibration Cert	ificates are issued in Accordance with	
	our Scope as gra	anted by NABL per ISO/IEC 17025:2017	
	Standards		
Set of Adaptors	<u>BSP</u>	<u>NPT</u>	
⅓" BSP	(F) X ¼" BSP (M)	½" NPT(F) X ¼" BSP (M)	
½" BSP	(F) X ¼" BSP (M)	¼" NPT(F) X ¼" BSP (M)	
¾" BSP	(F) X ¼" BSP (M)	½" NPT(F) X ¼" BSP (M)	
		%" NPT(F) X ¼" BSP (M)	

Manufactured by

NAGMAN INSTRUMENTS & ELECTRONICS (P) LTD.

Chennai-Bangalore National Highway, Nazarathpet P.O., Chembarambakkam, Chennai - 600 123. INDIA.

AN ISO 9001:2015 **CERTIFIED COMPANY**

Export Sales **Phone**: +91-44-66777006, 008.

Domestic Sales Phone: 044 – 66777020, 005, 021, 024. **Fax**: 044 – 66777050.

Fax: +91-44-66777050.

E-Mail: mktqchennai@nagman.com

E-Mail: exports@nagman.com

www.nagman.com