

## DUAL INPUT HUMIDITY TEMPERATURE METER

203

### Features :

- Dual Input
- Triple Display
- PC Interface
- REL Function
- Auto Power Off
- Hold Function
- Max/Min Function
- Resolution 0.1°C, 0.1°F, 0.1% RH

### Specifications :

Range & Accuracy	:	-20 ~ 60°C.....±0.7°C; -4 ~ 140°F.....±1.4°F
Temperature	:	-200 ~ 1370°C.....±0.3% rdg + 1°C;
(K-Type)	:	-328 ~ 2498°F.....±0.3% rdg + 2°F
Humidity	:	0 ~ 100% RH.....±2.5% RH
Resolution	:	0.1°C; 0.1°F ; 0.1% RH
Input Protection	:	60V DC or 24Vrms AC Maximum
Battery	:	9V battery
Dimensions	:	Meter : 186 x 64 x 30 mm Probe : 190 (L) x 15 (Dia) mm
Weight	:	Approx. 320 g
Sensor Type	:	K Type General Purpose Bead Probe Measurement Range : -50°C to 200°C; -58°F to 392°F; Tolerance : ±2.2°C (±3.9°F)



### Standard Delivery :

- Basic Instrument with Battery
- T/C Probe - 1 No.
- Traceable Calibration Certificate
- Instruction Manual

### Optional :

- USB Cable
- RS-232 Cable
- Software
- Calibration Certificates are issued in Accordance with our Scope as granted by NABL per ISO/IEC 17025:2017 Standards

Marketed by...



**NAGMAN INSTRUMENTS AND ELECTRONICS PRIVATE LIMITED.**

Chennai-Bangalore National Highway, Nazarethpet P.O., Chembarambakkam,  
Chennai – 600 123. INDIA.

**AN ISO 9001:2015  
CERTIFIED COMPANY**

Domestic Sales Phone : 044 – 66777020, 005, 021, 024.

E-Mail : [mktgchennai@nagman.com](mailto:mktgchennai@nagman.com)

Export Sales Phone : +91-44-66777025.

E-Mail : [exports@nagman.com](mailto:exports@nagman.com)

[www.nagman.com](http://www.nagman.com)