

TRMS INRUSH CLAMP METER

241

Features :

- With 0.01A High Resolution
- Measuring Frequency From Current Clamp & Test Terminal
- Inrush Function
- Back Light Function
- Data Hold Function
- Auto Power Off
- Auto ranging



Specifications :

Function	Range	Resolution	Accuracy
ACA	66A / 660A	0.01A / 0.1A	±1.9% rdg + 5 dgts
DCA	60A / 600A	0.01A / 0.1A	±2% rdg + 5 dgts
DCuA	600uA	0.1uA	±1% rdg +5 dgts
ACV	600V	0.1V	±1.2% rdg + 5 dgts
DCV	600V	0.1V	±1% rdg + 2 dgts
Ohms	660 ~ 6K	0.1 ~ 0.001K	±1% rdg + 2 dgts
Capacitance	400uF~4000uF	0.1uF ~ 1uF	±2.5% rdg + 5 dgts
Temp.	-50.0°C ~ 600.0°C	0.1°C	±1% rdg + 1.5°C
Hz(A)	660Hz ~ 30KHz	0.1Hz ~ 10Hz	±0.2% rdg + 1 dgts
Hz(v)	660Hz ~ 100KHz	0.1Hz ~ 0.1KHz	±0.2% rdg + 1 dgts
•)))	Active Sound Level: < 40		

Display	:	4 digit Liquid display, Maximum reading 6600
Sampling Rate	:	3 times/sec
Battery	:	1.5V size AAA battery x 2
Dimensions	:	209 x 74 x 36 mm
Weight	:	255 g
Maximum Jaw Opening	:	ø25 mm

Standard Delivery :

- Basic Instrument with Battery
- Test Lead
- Carrying Case
- Traceable Calibration Certificate
- Instruction Manual

Optional :

- Calibration Certificates are issued in Accordance with our Scope as granted by NABL per ISO/IEC 17025:2017 Standards

Marketed by...



Since 1972

NAGMAN INSTRUMENTS AND ELECTRONICS PRIVATE LIMITED.

Chennai-Bangalore National Highway, Nazarethpet P.O., Chembarambakkam,
Chennai – 600 123. INDIA.

AN ISO 9001:2015
CERTIFIED COMPANY

Domestic Sales Phone : 044 – 66777020, 005, 021, 024.

Export Sales Phone : +91-44-66777025.

E-Mail : mktgchennai@nagman.com

E-Mail : exports@nagman.com

www.nagman.com