Loop Calibrator with Hart Portable / Handheld

Nagman[®] 43H

Hart communicators provide the tool for communicating with process instruments. Relying on an open communications protocol, Hart communicators interface with Hart enabled 'master' and 'field' devices making it much easier to configure and calibrate instruments as well as diagnose issues before they collapse.

Support Hart general instructions and general application instructions. Able to read the device basic information, perform diagnostic testing and calibration to fine tune the most Hart transmitter, can store up to 20 Hart device configuration file.

SALIENT FEATURES

Protection grade : IP65	
Colour Display with Backlight	
Brightness Adjustment	
Automatic Ramp & Step	
Auto Power off	
Battery Low Display	

SPECIFICATIONS

Display	3.2 inch TFT color display
Power supply	4×1.5V AA Alkaline battery / adapter
Size (LxBxH)	206 × 97 × 60 mm
Weight (approx.)	600g



	Parameters		
Source Mode	DC current (DC mA)	Ranges	0.000 ~ 22.000mA
		Accuracy ±(% of the set value +% of range)	0.01% + 0.015%
		Resolution	1μΑ
	Analog Transmitter (Simulate)	Ranges	0.000 ~ 22.000mA
		Accuracy ±(% of the set value +% of range)	0.01% + 0.015%
		Resolution	1μΑ
		External power supply	5 ~ 28V
Measurement Mode	DC voltage (DC V)	Ranges	-2.000~28.000V
		Accuracy ±(% of Reading+% of Range)	0.01%+0.01%
		Resolution	1mV
	DC current (DC mA)	Ranges	-4.000 ~ 33.000mA
		Accuracy ±(% of Reading+% of Range)	0.01% + 0.01%
		Resolution	1μΑ
	Loop power supply (Loop)	Range	24V
		Maximum current	22mA
		Driving ability	No HART resistance of 1 K Ω . HART resistance is 750 Ω .

STANDARD INCLUSIONS

- Basic Instrument ٠
- Test Lead
- Crocodile Clip
- Alkaline Battery 4 Nos. •
- **Traceable Calibration Certificates** •
- Instruction Manual •

OPTIONAL (ADD-ON) ITEMS

Calibration Certificates are issued in Accordance with our Scope as granted by NABL per ISO/IEC 17025:2017 Standards •

Manufactured by

NAGMAN INSTRUMENTS & ELECTRONICS (P) LTD.



Chennai-Bangalore National Highway, Nazarathpet P.O., Chembarambakkam, Chennai – 600 123. INDIA.

Domestic Sales Phone : 044 – 66777020, 005, 021, 024. **Fax** : 044 – 66777050.
 Export Sales
 Phone : +91-44-66777006, 008.
 Fax : +91-44-66777050.
 E-Mail : exports@nagman.com

www.nagman.com

CERTIFIED COMPANY E-Mail : mktgchennai@nagman.com

AN ISO 9001:2015

Specifications subject to change owing to continuous development. Contact us for latest Datasheet. NIE/TDS/43H/01/00

July 2021