Technical Datasheet

Micro Liquid Bath

Portable / Benchtop Model

MLB-30 Stirred Bath

Ideal for Liquid-in-Glass Thermometers & Bi-Metal Thermometers / RTD Calibration

Site Calibration of Multiple / Multi-type / ODD Shaped Sensors (Lid / Probe holder can be designed to suit)

Stability & Precision of a Liquid Bath, Compact Size & Portability of a Dry Block Calibrator

SALIENT FEATURES

Compact, Portable / Bench-top Model
No Problems of Fitment / Immersion
Auto-tune PID Controller
Stirrer to ensure Temperature uniformity
(Oil) Spill proof Transport Lid
Overflow Outlet Provision
Computer Interface & Calibration Software – Optional

SPECIFICATIONS

Range	-30°C to 100°C
Resolution	0.1°C
Accuracy	±0.6°C
Stability	±0.2°C
Stabilisation Time	20 Minutes
Temperature Control	Auto-tune PID Controller
Temperature Readout	°C / °F Selectable
Working Chamber Dia	95 mm
Working Chamber Depth	170 mm
Chamber Capacity	1500 ml
Medium	-30°C to 50°C : Methanol **
	50°C to 100°C : Special Silicon Oil
Heating Time (Ambient to max.)	10 Minutes
Cooling Time (to 100°C)	30 Minutes
Power Supply / Consumption	230V AC / 50 Hz / 600 W
Housing / Mounting	Bench-top
Instrument Dimensions (W x D x H)	205 x 365 x 480 mm



STANDARD INCLUSIONS

- Basic Instrument with standard Lid / Probe Holder .
- Mains Cable •
- Spare Fuses
- Traceable Calibration Certificate •
- Instruction Manual
- Methanol ** (Customer scope, to be sourced locally)

OPTIONAL (ADD-ON) ITEMS

- **Computer Interface**
- "Caltemp" Calibration Software
- Lid / Probe Holder custom designed to suit
- 115V AC / 60 Hz Model
- Calibration Certificates are issued in Accordance with our Scope as granted by NABL per ISO/IEC 17025:2017 Standards

Manufactured by

NAGMAN INSTRUMENTS & ELECTRONICS (P) LTD.

Chennai – 600 123. INDIA.

Chennai-Bangalore National Highway, Nazarathpet P.O., Chembarambakkam,

AN ISO 9001:2015 **CERTIFIED COMPANY**

NAGMAN Since 1972

Domestic Sales Phone : 044 – 66777020, 005, 021, 024. **Fax** : 044 – 66777050. *Phone* : +91-44-66777006, 008. Export Sales

E-Mail : mktgchennai@nagman.com Fax : +91-44-66777050. E-Mail : exports@nagman.com

www.nagman.com

Specifications subject to change owing to continuous development. Contact us for latest Datasheet.

NIE/TDS/MLB 30/01/00

July 2021