Technical Datasheet

Medium Temperature Dry Block Calibrator Portable/Benchtop

Heavy Duty Models with an array of Interchangeable/Multihole Thermowells

Ideal for quick/fast Site Calibration of RTDs/TCs/Bi-Metal Thermometers, Temperature Switches/Indicators etc. in Industrial & Marine Applications

Meets the requirements of "Safety of Life at Sea" (SOLAS IX Maintenance Regulations) & "International Safety Management" (ISM)

SALIENT FEATURES

Heavy Duty Portable / Bench-top Model
Rugged Field Use & for Calibration at Site
Auto-tune PID Control
Switch Test facility
Fast and Reliable
Improved Accuracy, Resolution & Stability
Interchangeable Thermowell Inserts, Single / Multihole
Meets CE Norms



800-H

Heavy Duty

SPECIFICATIONS

ange	50°C to 800°C
esolution	0.1°C
ccuracy	Upto 600°C ±1.5°C; Above 600°C ±2.2°C
ability	±0.5°C
abilisation Time	25 Minutes
'ell Diameter	30 mm
mersion Depth	150 mm
ating Time (Ambient to max.) (approx.)	30 Minutes
oling Time Max. (to 100°C) (approx.)	75 Minutes
erchangeable Thermowells	Multihole to suit 2 x ¼" & 1 x ½" Probes. Other Sizes available as optional.
itch Test facility/Supply	Provided
wer Supply/Consumption	230V AC/50 Hz/1400 W
strument Dimensions (L x D x H)	160 x 330 x 350 mm
strument Weight	14 Kg.

STANDARD INCLUSIONS

- Basic Instrument
- Test Leads
- Mains Cable
- Multi-hole Insert to suit $2x\frac{1}{4}$ " + $1x\frac{1}{2}$ " Probes
- Tool for Insertion Tubes

- Spare Fuses
- **Traceable Calibration Certificate**
- Instruction Manual
- **Carrying Case**

OPTIONAL (ADD-ON) ITEMS

- **Computer Interface** •
- "Caltemp" Calibration Software .
- Additional Thermowells / Insertion Tubes (to choose from) Multihole (Typical) : (1x6 + 1x8) or (3x6) or (1x10 + 1x4) mm .
- Dual Voltage selection (110V AC & 230V AC)
- Calibration Certificates are issued in Accordance with our Scope as granted by NABL per ISO/IEC 17025:2017 Standards

Manufactured by





170/1a2, Chennai Bangalore Highway Road, Sembarambakkam, Chennai – 600 123. INDIA.

Phone - Domestic Sales 044–6677 7024, 044–6677 7005 Email : mktgchennai@nagman.com Email : exports@nagman.com **Phone - Export Sales** +91-44-6677 7025.

www.nagman.com

Specifications subject to change owing to continuous development. Contact us for latest Datasheet.

NIE/TDS/800-H/01/01

11/22