Comparison Testers

GCH Series Portable / Bench-top Models

Screw Pumps

Useful for checking Pressure Measuring Devices / Master Devices / Test Gauges

SALIENT FEATURES

Budget Solutions
Very Low Maintenance Cost
Compact & Easy to carry for Lab & Field use
Priming Pump with Fine Adjustment Vernier for Incremental Pressure generation

Typical Photo;

Final product look may vary

Gauge / Indicator not part of Standard Equipment



SPECIFICATIONS

Adjustable Foot

Ranges	0 to 1200 / 1400 / 1700 / 2000 bar
Туре	Screw Pump
Pressure generation	Priming Pump for initial pressures & Screw RAM Pump for high pressures
Test Port Connection	½" BSP (F) Swivel
Medium	Oil (Optional : Water) #
Dimensions	530 x 480 x 230 mm (L x D x H)
Weight	19 Kg.

STANDARD INCLUSIONS

- **Basic Instrument**
- Hydraulic Fluid (500 ml)
- Set of Seals
- Conformance Certificate
- Instruction Manual

OPTIONAL (ADD-ON) ITEMS

- Analog or Digital Master Gauges
- Distilled Water #
- Set of Adaptors 1/8" BSP(F) X 1/2" BSP (M) 1/4" BSP(F) X 1/2" BSP (M) BSP 3/8" BSP(F) X 1/2" BSP (M) 1/8" NPT(F) X 1/2" BSP (M) 1/4" NPT(F) X 1/2" BSP (M) NPT 1/2" NPT(F) X 1/2" BSP (M) 3/8" NPT(F) X 1/2" BSP (M)

Right Angled & Two Gauge Adaptors

Manufactured by

NAGMAN INSTRUMENTS AND ELECTRONICS PRIVATE LIMITED

AN ISO 9001:2015 CERTIFIED COMPANY

170/1a2, Chennai Bangalore Highway Road, Sembarambakkam, Chennai – 600 123. INDIA.

Phone - Export Sales

Phone - Domestic Sales 044–6677 7024, 044–6677 7005 **Email**: <u>mktgchennai@nagman.com</u> Email: exports@nagman.com +91-44-6677 7025.





NAGMAN Since 1972

Specifications subject to change owing to continuous development. Contact us for latest Datasheet.

NIE/TDS/GCH Series/2309/00