Combined Vacuum & Pressure Hand Pump

Pneumatio

PHP 60
Handheld/Table-top

Ideal tool for checking & Calibration of Pneumatic Digital Indicators, Manometers, Pressure Transducers / Transmitters, Pneumatic Loops etc.

Generates (Pneumatic) Pressure / Vacuum thro' convenient Scissor action / minimum effort, Fine Adjustment Vernier.

SALIENT FEATURES

Compact, Light Weight, Hand Operated
Combined Vacuum & Pressure Pump with Pressure/Vacuum Changeover option
Fine Adjustment Vernier to realize upto 1 mbar Resolution/Sensitivity
Very Low Leakage rate
Flexible Nylon Hose (1 Meter) with Swivel Adaptor to connect devices under test

SPECIFICATIONS

Range	-0.9 bar Vacuum to 60 bar Pressure
Medium	Air
Sensitivity / Resolution	Upto 1 mbar
Gauge / Indicator Connection Port	3/8" (F) BSP
Test Connection Port	1/4" (F) BSP
Instrument Dimension	240 x 160 x 65 mm (H x W x D)
Instrument Weight (approx.)	1 Kg

STANDARD INCLUSIONS

- Basic Pump
- Nylon Hose (1 Meter)
- Set of Seals
- Conformance Certificate
- Instruction Manual

OPTIONAL (ADD-ON) ITEMS

- Carrying Case (Soft)
- Analog / Digital Pressure Gauges
- Quick Connector
- Spare Seals Kit
 - Set of Adaptors

 %" BSP(F) X %" BSP (M)

 ½" BSP(F) X %" BSP (M)

 %" BSP(F) X %" BSP (M)

 %" NPT(F) X %" BSP (M)

 %" NPT(F) X %" BSP (M)

 ½" NPT(F) X %" BSP (M)

 ½" NPT(F) X %" BSP (M)

 %" NPT(F) X %" BSP (M)

Typical Photo; Final Product look may vary



Manufactured by

NAGMAN

NAGMAN INSTRUMENTS AND ELECTRONICS PRIVATE LIMITED

AN ISO 9001:2015 CERTIFIED COMPANY

170/1a2, Chennai Bangalore Highway Road, Sembarambakkam, Chennai – 600 123. INDIA.

 Phone - Domestic Sales
 044-6677 7024, 044-6677 7005
 Email: mktgchennai@nagman.com

 Phone - Export Sales
 +91-44-6677 7025.
 Email: exports@nagman.com

Since 1972 <u>www.nagmar</u>



Specifications subject to change owing to continuous development. Contact us for latest Datasheet.

NIE/TDS/PHP 60/2309/00