Technical Datasheet

Portable Dual Pressure Calibrator

Heavy Duty - Dual - Pneumatic & Hydraulic

Ideal Lab / Site Tool for checking & Calibration of Pressure / Differential Pressure Gauges / Transmitters / Indicators / Loops, Pneumatic Receiver Gauges, Control Valves, Pressure / Transducers etc.- in Industrial & Marine Applications

SALIENT FEATURES

Light Weight & Compact	
Unique Combo 2-in-1 Space Saver	
Housed in Rugged Carry Case	
Automatic Temperature Compensation (0 to 50°C)	
4.3" Colour Display with Touch Screen	
Selectable Engineering Pressure Units	
DC Current & Voltage Measurement	
Switch Test capability & Zero Offset facility	
Audio & Visual Alarms for Over Pressure	
Pressure Transducer – all Media compatible with SS316	
Rechargeable Battery with 'Low Battery' indication	
Digital Pressure Indicator with 2 integral / built-in Pumps & Fine Adjustment Vernier	
Ingress Protection IP 65	



PPC-D

Table-top / Bench-top

SPECIFICATIONS

-0.85 bar Vacuum to 20 bar (Pneumatic) & 0 to 400 bar (Hydraulic) (Oil) Ranges Accuracy ±0.05% F.S. **Temperature Compensation** 0 to 50°C (Automatic) Minimum 5 digits **Display Resolution** Display 4.3" Colour Display with Touch Screen Kg/cm2, bar, mbar, PSI, mH2O, mmH2O, cmH2O, inH2O, ftH2O, mmHg, inHg, Atm, Mpa, Kpa, Pa **Engineering Units** 4 - 20 mA, 0 - 50 mA (Active Loop) & 0 - 25 mA (Passive Loop); Loop Supply Provided mA Input Volt Input 0 to 10V DC Resolution (mA / V) 0.001 **Pressure Switch Test** Maximum 5V DC (approx.) Medium Air & Oil (Water : optional) # **Over Pressure Alarm** 105% FS (Audio / Visual) Instrument Dimension 425 x 335 x 200 mm (L x B x H) Instrument Weight (approx..) 10 Kg.

	ST	ANDARD II	NCLUSION	S		
Digital Pressure Cali Test Leads & Seals K		Hose with External (ng (Pneumatio	& Hydraulic)	"Calpress
Oil : 250 ml		Traceable Calibration Certificate			Calibratio	
Instruction Manual		Compute	r Interface			with our S
Set of Adaptors		<u>BSP</u>		<u>N</u>	<u>PT</u>	17025:20
) X ¼" BSP	• •	1∕8″ NPT(F) X	· · ·	
) X ¼" BSP	• •	¼" NPT(F) X	· · /	Water Op
	¾″ BSP(F) X ¼" BSP	(M)	½" NPT(F) X	¼" BSP (M)	

OPTIONAL (ADD-ON) ITEMS

s" Calibration Software with Cable

on Certificates are issued in Accordance Scope as granted by NABL per ISO/IEC 017 Standards

perated #

Manufactured by



NAGMAN INSTRUMENTS AND ELECTRONICS PRIVATE LIMITED AN ISO 9001:2015 CERTIFIED COMPANY

¾" NPT(F) X ¼" BSP (M)

170/1a2, Chennai Bangalore Highway Road, Sembarambakkam, Chennai – 600 123. INDIA.

Since 1972

Phone - Domestic Sales 044–6677 7024, 044–6677 7005 Email : mktgchennai@nagman.com Phone - Export Sales +91-44-6677 7025. Email : exports@nagman.com



Specifications subject to change owing to continuous development. Contact us for latest Datasheet.

NIE/TDS/PPC-D/2309/00

02/24