

DUAL INPUT HUMIDITY TEMPERATURE METER

203

Features :

- Dual Input
- Triple Display
- PC Interface
- REL Function
- Auto Power Off
- Hold Function
- Max/Min Function
- Resolution 0.1°C, 0.1°F, 0.1% RH (upto 200°C 1°C, 1°F above 200°C)

Specifications :

Range & Accuracy	-20 ~ 60°C.....±0.7°C; -4 ~ 140°F±1.4°F
Temperature	-200 ~ 1370°C.....±0.3% rdg + 1°C/0.5°
(K-Type)	-328 ~ 2498°F.....±0.3% rdg + 2°F/0.5°
Humidity	10 ~ 90% RH.....±2.5% RH/0.5°
Resolution	0.1°C -200 ~ 200°C; 1° = 200 ~ 1370°; 0.1°F = 200 ~ 200°F; 1°F = Else
Input Protection	60V DC or 24Vrms AC Maximum
Battery	9V battery
Dimensions	Meter : 186 x 64 x 30 mm Probe : 190 (L) x 15 (Dia) mm
Weight	Approx. 320 g
Sensor Type	K Type General Purpose Bead Probe Measurement Range : -50°C to 200°C; -58°F to 392°F; Tolerance : ±2.2°C (±3.9°F)



Standard Delivery :

- Basic Instrument with Battery
- T/C Probe - 1 No.
- Traceable Calibration Certificate
- Instruction Manual

Optional :

- USB Cable
- RS-232 Cable
- Software
- Calibration Certificates are issued in Accordance with our Scope as granted by NABL per ISO/IEC 17025:2017 Standards

Manufactured by



Since 1972

NAGMAN INSTRUMENTS AND ELECTRONICS PRIVATE LIMITED

AN ISO 9001:2015 CERTIFIED COMPANY

170/1a2, Chennai Bangalore Highway Road, Sembambakkam, Chennai – 600 123. INDIA.

Phone - Domestic Sales 044-6677 7024, 044-6677 7005 Email : mktchennai@nagman.com
Phone - Export Sales +91-44-6677 7025. Email : exports@nagman.com

www.nagman.com

