

DATALOGGER DUAL INPUT HUMIDITY TEMPERATURE METER

204

Features :

- Dual Input
- Triple Display
- PC Interface
- 16,000 Records Data Logger Per Channel
- Auto Power Off
- Clock Function
- Hold Function
- Max/Min Function
- Resolution 0.1°C, 0.1°F (upto 20°C/°F), 0.1%RH (1°/1°F above 20°C)

Specifications :

Range & Accuracy	-20 ~ 60°C.....±0.7°C; -4 ~ 140°F±1.4°F
Temperature	-200 ~ 1370°C.....±0.3% rdg + 1°C/0.5°
(K-Type)	-328 ~ 2498°F.....±0.3% rdg + 2°F/0.5°
Humidity	10 ~ 90% RH.....±2.5% RH/0.5°
Resolution	0.1°C; 0.1°F; 0.1%RH
Input Protection	60V DC or 24Vrms AC Maximum
Battery	9V battery
Dimensions	Meter : 186 x 64 x 30 mm Probe : 190 (L) x 15 (Dia) mm
Weight	Approx. 320 g
Sensor Type	K Type General Purpose Bead Probe Measurement Range : -50°C to 200°C; -58°F to 392°F; Tolerance : ±2.2°C (±3.9°F)



Standard Delivery :

- Basic Instrument with Battery
- T/C Probe - 1 No.
- Carrying Case
- RS-232 Cable
- Software
- Traceable Calibration Certificate
- Instruction Manual

Optional :

- AC Adaptor
- USB Connection Cable
- Calibration Certificates are issued in Accordance with our Scope as granted by NABL per ISO/IEC 17025:2017 Standards

Manufactured by



Since 1972

NAGMAN INSTRUMENTS AND ELECTRONICS PRIVATE LIMITED

AN ISO 9001:2015 CERTIFIED COMPANY

170/1a2, Chennai Bangalore Highway Road, Sembarambakkam, Chennai – 600 123. INDIA.

Phone - Domestic Sales 044-6677 7024, 044-6677 7005 Email : mktchennai@nagman.com

Phone - Export Sales +91-44-6677 7025. Email : exports@nagman.com

www.nagman.com

