4 CHANNELS DATA LOGGER THERMOMETER

Features:

- Supports K, J, E, T Thermocouple Probe
- **Data Hold Function**
- Temperature Alarm Function
- Adjustable Auto Power Off Timer
- Fast Response With High Accuracy
- Measures K, J, E, T Type Thermocouples
- Min/Max/Avg Recording of All Channels
- USB Interface, PC Software Included
- Large Backlit LCD Shows All Channels On Display
- Datalogging Up to 16,000 Points Each Channel
- Recall Function to Instantly Read-out Up to 100 Sets Manually Saved Data



Specifications:

Range	-200 ~ 1370°C; -328 ~ 2498°F below -100°C (-148°C)
Accuracy	$\pm 0.1\%$ rdg + 0.7°C, $\pm 0.1\%$ + 1.4°F below 100, 0.4% of reading + 0.7°C; $\pm 0.4\%$ of reading + 1.4°F
Resolution	0.1°C < 600°C / 0.1°F < 1000°F
	1°C ≥ 600°C / 1°F ≥ 1000°F
Operation Temp	0°C ~ 50°C (<80% RH)
Storage Temp	-20°C ~ 60°C (<70% RH)
Battery	1.5V, Size AAA battery x 4
Dimensions	187 x 75 x 29 mm
Weight	Approx.290g
Sensor Type	K Type General Purpose Bead Probe
	Measurement Range: -50°C to 200°C; -58°F to 392°F;
	Tolerance: ±2.2°C (±3.9°F)

Standard Delivery:

- Basic Instrument with Battery
- K Type Probe x 2 Nos.
- **Carrying Case**
- Micro USB Cable
- Software
- Traceable Calibration Certificate
- Instruction Manual

Optional:

Calibration Certificates are issued in Accordance with our Scope as granted by NABL per ISO/IEC 17025:2017 Standards

Manufactured by



NAGMAN INSTRUMENTS AND ELECTRONICS PRIVATE LIMITED

AN ISO 9001:2015 CERTIFIED COMPANY

170/1a2, Chennai Bangalore Highway Road, Sembarambakkam, Chennai – 600 123. INDIA.

Phone - Domestic Sales 044–6677 7024, 044–6677 7005 **Email**: <u>mktqchennai@nagman.com</u> Phone - Export Sales +91-44-6677 7025. Email: exports@nagman.com



