

## Ultrasonic Thickness Gauge

225

The thickness of any good conductor for Ultrasonic Waves with top & bottom surfaces parallel to each other, like metal, plastic, ceramic & glass, can be measured with the instrument (ex.: Aluminium, Copper, Gold, Resin, Water, Glycerin etc.). The internal particles of cast iron are too big for this instrument.

### SALIENT FEATURES

Menu Operation  
 Color Screen HD Display  
 Storage Function  
 Screen Brightness Selection  
 Automatic Shutdown Selection Function

### SPECIFICATIONS

Measuring range	1.00 ~ 225.0 mm
Data storage	500
Operation frequency	5MHz
Measurement error	±(0.5% H + 0.05) mm
Resolution	0.01 mm (1.00 to 99.99mm); 0.1mm (100 to 225 mm)
Lower limit of pipe measurement	Φ20 x 3 mm (steel)
Adjustment range of sound speed	1000 ~ 9999m/s
Temperature range of operation	0 ~ 40°C
Battery	3 Nos. Ni-MH rechargeable batteries of 1.2V
USB charging	5V 1A
Dimensions (LxHxD)	65 x 146 x 30 mm
Weight	130 G
Probe	Measurement parameters
5M-d10	1.0 ~ 225.0mm

### STANDARD INCLUSIONS

- Color Box
- PP Box
- Host
- USB Cable
- Coupling Agent
- Plug
- Ni-MH rechargeable battery - 3 Nos.
- Probe
- Instruction Manual

### OPTIONAL ITEMS (ADD ONS)

- Calibration Certificates are issued in Accordance with our Scope as granted by NABL per ISO/IEC 17025:2017 Standards

Manufactured by



**NAGMAN INSTRUMENTS AND ELECTRONICS PRIVATE LIMITED**

**AN ISO 9001:2015 CERTIFIED COMPANY**

170/1a2, Chennai Bangalore Highway Road, Sembarambakkam, Chennai – 600 123. INDIA.

Phone - Domestic Sales 044-6677 7024, 044-6677 7005 Email : [mkt@chennai@naqman.com](mailto:mkt@chennai@naqman.com)

Phone - Export Sales +91-44-6677 7025. Email : [exports@naqman.com](mailto:exports@naqman.com)

Since 1972

[www.nagman.com](http://www.nagman.com)

