

TRMS MILLI-AMP AC/DC CLAMP METER (0.1mA)

244

Features :

- 0.1 mA Current Resolution @ 300 mA
- True RMS Measurement For All Applications
- Backlight Function
- MAX MIN Measurement Function
- Data Hold Function
- Zero Function
- Auto Power Off
- Autoranging

Specifications :

Function	Range	Resolution	Accuracy
DCA	3.00.0 mA / 300.0 mA / 3 A / 10.00 A	0.1mA / 1mA / 0.01A	± 1% rdg ± 10 dgts / 3.0% + 10 dgts
ACA	3.00.0 mA / 300.0 mA / 3 A / 20.00 A	0.1mA / 1mA / 0.01A	± 1% rdg ± 5 dgts
DCV	50V / 300V	0.01V / 0.1V	±1% rdg ± 2 dgts
ACV	50V / 300V	0.01V / 0.1V	± 1% rdg ± 5 dgts
Ohms	500Ω / 5KΩ / 50KΩ / 500KΩ	0.1Ω / 1Ω / 10Ω / 100Ω	±1% rdg ± 2 dgts
•)))_Active Sound Level	< 100Ω		

Display : 4 digital Liquid display
 Sampling Rate : 2 times/sec
 Battery : 1.5V size AAA battery x 2
 Dimensions : 206 x 76 x 33.5 mm
 Weight : 270 g
 Maximum Jaw Opening : ø 23 mm

Standard Delivery :

- Basic Instrument with Battery
- Test Lead
- Carrying Case
- Traceable Calibration Certificate
- Instruction Manual

Optional :

- Calibration Certificates are issued in Accordance with our Scope as granted by NABL per ISO/IEC 17025:2017 Standards



Manufactured by



Since 1972

NAGMAN INSTRUMENTS AND ELECTRONICS PRIVATE LIMITED

AN ISO 9001:2015 CERTIFIED COMPANY

170/1a2, Chennai Bangalore Highway Road, Sembambakkam, Chennai – 600 123. INDIA.

Phone - Domestic Sales

044-6677 7024, 044-6677 7005

Email : mktachennai@naqman.com

Phone - Export Sales

+91-44-6677 7025.

Email : exports@naqman.com

www.nagman.com

