

TRMS AC DC Clamp Meter

245

Features :

- True RMS
- Autoranging
- Auto Power Off
- High Speed Bargraph available
- Data Hold Function
- Peak Hold Function



Specifications :

Function	Range	Resolution	Accuracy
ACA	40A ~ 1000A	0.01A ~ 1A	±1.9% reading + 5 digits
DCA	40A ~ 1000A	0.01A ~ 1A	±2% reading + 10 digits
ACV	400V ~ 750V	0.1V ~ 1V	±1.5% reading + 5 digits
DCV	400V ~ 1000V	0.1V ~ 1V	±1% reading + 2 digits
Ohms	400Ω ~ 4000Ω	0.1Ω ~ 1Ω	±1% reading + 3 digits
Hz(A)	4KHz ~ 10KHz	1Hz	±0.1% reading + 1 digits
Hz(v)	4KHz ~ 10KHz	1Hz	±0.1% reading + 1 digits

•)))	:	Active Sound Level : $\leq 100\Omega$
Display	:	3-3/4 digital Liquid display, Maximum reading 3999
Sampling Rate	:	2 times/sec (digital reading); 20 times/sec (analog bar indication)
Battery	:	9V battery
Dimensions	:	242 x 66 x 36 mm
Weight	:	400g
Maximum Jaw Opening :	:	40 mm

Standard Delivery :

Basic Instrument with Battery
 Test Lead
 Carrying Case
 Traceable Calibration Certificate
 Instruction Manual

Optional :

Calibration Certificates are issued in Accordance with our Scope as granted by NABL per ISO/IEC 17025:2017 Standards

Manufactured by



Since 1972

NAGMAN INSTRUMENTS AND ELECTRONICS PRIVATE LIMITED

AN ISO 9001:2015 CERTIFIED COMPANY

170/1a2, Chennai Bangalore Highway Road, Sembarambakkam, Chennai – 600 123. INDIA.

Phone - Domestic Sales 044-6677 7024, 044-6677 7005 Email : mktgchennai@nagman.com
 Phone - Export Sales +91-44-6677 7025. Email : exports@nagman.com

www.nagman.com

