

Digital Multimeter

281

Features :

- 3¾ Digits Display
- Autoranging
- High Speed Bargraph
- Max/Min Function
- REL Function
- AC/DC 10A Test

Specifications :

Function	Range	Resolution	Accuracy
DCV	400mV ~ 1000V	0.1mV ~ 1V	±0.5% rdg + 2 digits / 0.8% rdg + 2 digits
ACV	400mV ~ 750V	0.1mV ~ 1V	1% rdg + 4 digits
DCA	400uA ~ 10A	0.1uA ~ 0.01A	±1.2% + 2 digits
ACA	400uA ~ 10A	0.1uA ~ 0.01A	±1.5% rdg + 5 digits
Ohms	400Ω ~ 40MΩ	0.1Ω ~ 10KΩ	±0.75% + 2 digits / 1.2% + 3 digits
Hz	4KHz ~ 40MHz	1Hz ~ 10KHz	±0.1% rdg + 1 digit



- | - : 1mA
-)))_Active Sound Level : ≤ 40Ω
- Sampling Rate : 2 times/sec for digital reading; 20 times/sec for analog bar indication
- Battery : 1.5V size AAA battery x 2
- Dimensions : 150 x 72 x 35 mm
- Weight (with holster) : 220g

Standard Delivery :

Basic Instrument with Battery
 Test Lead
 Traceable Calibration Certificate
 Instruction Manual

Optional :

Calibration Certificates are issued in Accordance with our Scope as granted by NABL per ISO/IEC 17025:2017 Standards

Marketed by...



Since 1972

NAGMAN INSTRUMENTS AND ELECTRONICS PRIVATE LIMITED.

Chennai-Bangalore National Highway, Nazarethpet P.O., Chembarambakkam,
 Chennai – 600 123. INDIA.

AN ISO 9001:2015
 CERTIFIED COMPANY

Domestic Sales Phone : 044 – 66777020, 005, 021, 024.

Export Sales Phone : +91-44-66777025.

E-Mail : mktgchennai@nagman.com

E-Mail : exports@nagman.com

www.nagman.com

Specifications subject to change owing to continuous development. Contact us for latest Datasheet.

NIE/TDS/281/2309/00