

TRMS AC INRUSH CLAMP METER**NAGMAN 241****SALIENT FEATURES**

With 0.01A High Resolution 0.01 – 66A; 0.1 – 660A
 Measuring Frequency from Current Clamp & Test Terminal
 Inrush Function
 Back Light Function
 Data Hold Function
 Auto Power Off
 Auto ranging

GENERAL SPECIFICATIONS

Function	Range	Resolution	Accuracy
ACA	66A	0.01A	±1.9% reading + 5 digits
	660A	0.1A	
ACV	600V	0.1V	±1.2% reading + 5 digits
DCV	600V	0.1V	±1% reading + 2 digits
Ohms	660Ω	0.1Ω	±1% reading + 2 digits
Hz(A)	660Hz ~ 30KHz	0.001 – 0.1	±0.2% reading + 1 digits (Sensitivity: 3 Arms)
Hz(v)	660Hz ~ 100KHz	0.0001 – 0.1	±0.2% reading + 1 digits (Sensitivity: 5 Vrms)
•)))	Ohm function Buzzer < 30Ω		

Display	4-digit Liquid display, Maximum reading 6600
Sampling Rate	3 times/sec
Battery	1.5V size AAA battery x 2
Dimensions	210 x 62 x 36 mm
Weight	255 g
Maximum Jaw Opening	ø25 mm



Typical Photo: Final Product look may vary

STANDARD INCLUSIONS

- Basic Instrument with Battery
- Test Lead
- Carrying Case
- Conformance Certificate
- Instruction Manual

OPTIONAL

- Calibration Certificates are issued in Accordance with our Scope as granted by NABL per ISO/IEC 17025:2017 Standards

Manufactured by



NAGMAN INSTRUMENTS AND ELECTRONICS PRIVATE LIMITED

AN ISO 9001:2015 CERTIFIED COMPANY

170/1a2, Chennai Bangalore Highway Road, Sembarambakkam, Chennai – 600 123. INDIA

Phone - Domestic Sales 044-6677 7024, 044-6677 7005

Email: mktgchennai@nagman.com

Phone - Export Sales +91-44-6677 7025.

Email: exports@nagman.com

www.nagman.com

