

TRMS AC LEAKAGE CLAMP METER (0.001mA)**NAGMAN 246****SALIENT FEATURES**

mA Current Resolution
True RMS Measurement for all Applications
Low Pass Filter Function
Backlight Function
Peak Hold Function
Data Hold Function
Zero Function
Auto Power Off

GENERAL SPECIFICATIONS

Function	Range	Resolution	Accuracy
ACmA	6.000mA / 60.00mA / 600.0mA	0.001mA / 0.01mA / 0.1A	±1% rdg ±3 dgts
ACA	6.000A / 60.00A	0.001A / 0.01A	±1% rdg ±3 dgts
DCV	60V / 600V	0.01V / 0.1V	±1% rdg ±2 dgts
ACV	60V / 600V	0.01V / 0.1V	±1% rdg ±3 dgts
Ohms	600Ω / 6KΩ / 60KΩ / 600KΩ	0.1Ω / 1Ω / 10Ω / 100Ω	±1% rdg ±2 dgts

•)))	Active Sound Level: < 60Ω
Display	4 digital Liquid display, Maximum reading 6000
Sampling Rate	2 times/sec
Battery	1.5V size AAA battery x 2
Dimensions	206 x 76 x 33.5 mm
Weight	270g
Maximum Jaw Opening	ø 23 mm



Typical Photo: Final Product look may vary

STANDARD INCLUSIONS

- Basic Instrument with Battery
- Test Lead
- Carrying Case
- Conformance Certificate
- Instruction Manual

OPTIONAL

- Calibration Certificates are issued in Accordance with our Scope as granted by NABL per ISO/IEC 17025:2017 Standards

Manufactured by



Since 1972

NAGMAN INSTRUMENTS AND ELECTRONICS PRIVATE LIMITED

AN ISO 9001:2015 CERTIFIED COMPANY

170/1a2, Chennai Bangalore Highway Road, Sembarambakkam, Chennai – 600 123. INDIA

Phone - Domestic Sales 044-6677 7024, 044-6677 7005 Email: mktgchennai@nagman.com

Phone - Export Sales +91-44-6677 7025.

Email: exports@nagman.com

www.nagman.com

