

REFRIGERANT LEAKAGE DETECTOR

NAGMAN 273

GENERAL SPECIFICATIONS

Heated Semiconductor Gas Sensor
High-Low Leak Sensitivity Selector
7 LED Tri-colored Visual Leak Level Indicator
Variable Intensity Audible Alarm
Ambient Concentration Reset
15.5"(40CM) Flexible Stainless Probe
Detection of R134a, R404A, R410A, R600A, R290, R407C, R22, R32, HFO-1234yf Refrigerants Gas
Sensitivity As Small 6gr/year
Accordance With SAE J1627, CE Design
Low Battery Indication
Reference Leak Source Included
Operating Temperature : 0 to 40°C(32 to 104°F)
Power Source : AA Size Alkaline Batteries x 4
Battery Life : Approx. 40 hrs
Size : 21.7 x 6.6 x 5.6 cm
Weight : 400g(with batteries)



Typical Photo: Final Product look may vary

STANDARD INCLUSIONS

- Basic Instrument with Battery
- Carrying Case
- Leak Check Bottle
- Conformance Certificate
- Instruction Manual

Manufactured by



Since 1972

NAGMAN INSTRUMENTS AND ELECTRONICS PRIVATE LIMITED

AN ISO 9001:2015 CERTIFIED COMPANY

170/1a2, Chennai Bangalore Highway Road, Sembarambakkam, Chennai – 600 123. INDIA

Phone - Domestic Sales 044-6677 7024, 044-6677 7005 Email: mktgchennai@nagman.com

Phone - Export Sales +91-44-6677 7025. Email: exports@nagman.com

www.nagman.com



Specifications subject to change owing to continuous development. Contact us for latest Datasheet.

NIE/TDS/273/06/26/00