

Comparison Testers

Hydraulic

GCL / GCH Series

Portable / Bench-top Models

Screw Pumps

Useful for checking Pressure Measuring Devices / Master Devices / Test Gauges



SALIENT FEATURES

- Budget Solutions
- Very Low Maintenance Cost
- Compact & Easy to carry for Lab & Field use
- Priming Pump with Fine Adjustment Vernier for Incremental Pressure generation
- Adjustable Foot

SPECIFICATIONS

Ranges	0 to 250 / 350 bar (GCL-SP Series). 0 to 700 / 1000 bar (GCH-SP Series)
Type	Screw Pump
Pressure generation	Priming Pump for initial pressures & Screw RAM Pump for high pressures
Test Port Connection	M26 X 3 mm Pitch(M)
Medium	Oil (Optional: Water) #
Dimensions	460 x 360 x 200 mm (L x D x H)
Weight	14 Kg (Approx).

STANDARD INCLUSIONS

- Basic Instrument
- Hydraulic Fluid (500 ml)
- Set of Seals
- Conformance Certificate
- Instruction Manual
- Set of Adaptors - SS
M26 (F) X 1/2" BSP(F) 2 Nos.

OPTIONAL (ADD-ON) ITEMS

- Analog or Digital Master Gauges
- Distilled Water #
- Right Angled & Two Gauge Adaptors
- Set of Adaptors - SS
 - M26 (F) X 1/8" BSP(F)
 - M26 (F) X 1/4" BSP(F)
 - M26 (F) X 3/8" BSP(F)
 - M26 (F) X 1/2" BSP(F)
 - M26 (F) X 3/4" NPT(F)
 - M26 (F) X 1" NPT(F)
 - M26 (F) X 1 1/2" NPT(F)
 - M26 (F) X 2" NPT(F)



Typical Photo. Final product look may vary. Gauges are not part of standard delivery.

Manufactured by



Since 1972

NAGMAN INSTRUMENTS AND ELECTRONICS PRIVATE LIMITED

AN ISO 9001:2015 CERTIFIED COMPANY

170/1a2, Chennai Bangalore Highway Road, Sembarambakkam, Chennai – 600 123. INDIA.

Phone - Domestic Sales
Phone - Export Sales

044-6677 7024, 044-6677 7005
+91-44-6677 7025.

Email: mktachennai@nagman.com
Email: exports@nagman.com

www.nagman.com

